

Drop S 5W

DROP XX
recessed empotrado

495Lm / 2700K-4000K

Ip20 / CRI ≥ 90 / 24°

7lumen
create the light



DESCRIPTION DESCRIPCIÓN

At first sight Drop appears to be simple. In close-up, the workmanship is being revealed in the little details. The refined ratio of the body compared to its diameter, the small joints that create a sophisticated look, the softly curved hinge that perfectly matches the contours of its body. With Drop, elegance is in the details.

REFERENCES REFERENCIAS

DROP S /27	2700K	398Lm	79.6Lm/W
DROP S /30	3000K	429Lm	85,8Lm/W
DROP S /40	4000K	495Lm	99,8Lm/W

GENERAL

negro black blanco white

recessed empotrado

Ip20

IK07

ELECTRICAL ELÉCTRICA

05W

220-240VAC 50/60Hz

equipo incluido

gear included

LIGHTING FIXTURE

APARATO DE ILUMINACIÓN

24°

CRI ≥ 90

Ip20

MacAdam ≤ 3

UGR <19

difusor transparente

clear diffuser

power values of the system (LED + driver): 5,0W

valores de potencia del sistema (LED + driver): 5,0W

MEASURES MEDIDAS

Base (∅) 55mm, Shaft (∅) 25mm

altura: 155mm

height: 155mm

DIMMING REGULACIÓN

on / off

phase-cut dimming IGBT/TRIAC

corte de fase IGBT/TRIAC

1-10V

push

pulsador

DALI

ACCESSORIES ACCESORIOS

no disponible

not available

CUTOUT RECORTE

50mm

min. espesor del techo: 1mm


min. ceiling thickness: 1mm

máx. espesor del techo: 31mm

max. ceiling thickness: 31mm

profundidad empotrada: 55mm

recessed depth: 55mm



H(m)	D(cm)	Lux
1	27	1041
2	55	546
3	82	121

3000K 15°



change without notice cambio sin previo aviso