

Minima R10 10W

MINIMA RX
recessed empotrado

1217Lm / 2700K-4000K
IP40 / CRI ≥ 80 / 24° 38°

7lumen
create the light

DESCRIPTION DESCRIPCIÓN

Downlight with a "anti-glare effect" thanks to its very high position of the source of the source



GENERAL

negro black blanco white

recessed empotrado

IP40

IK07

LIGHTING FIXTURE

APARATO DE ILUMINACIÓN

24° 38°

CRI ≥ 80

IP40

MacAdam ≤ 3

UGR <19

difusor transparente

clear diffuser

power values of the system (LED + driver): 10,0W

valores de potencia del sistema (LED + driver): 10,0W

ACCESSORIES ACCESORIOS

no disponible

not available

ELECTRICAL ELÉCTRICA

10W

220-240VAC 50/60Hz

equipo incluido

gear included

MEASURES MEDIDAS

día: 93mm

altura: 82mm

height: 39mm

DIMMING REGULACIÓN

on / off

phase-cut dimming IGBT/TRIAC

corte de fase IGBT/TRIAC

1-10V

push

pulsador

DALI

CUTOUT RECORTE

día:85mm

min. espesor del techo: 13mm

min. ceiling thickness: 13mm

máx. espesor del techo: 44mm


max. ceiling thickness: 44mm

profundidad empotrada: 105mm

recessed depth: 105mm

REFERENCES REFERENCIAS

MINIMA R10/27	2700K	1080Lm	90Lm/W
MINIMA R10/30	3000K	1217Lm	101,4Lm/W
MINIMA R10/40	4000K	1318Lm	109,8Lm/W



H(m)	D(cm)	Lux
1	45	4037
2	90	1009
3	135	449

3000K 24°

H(m)	D(cm)	Lux
1	69	2969
2	138	742
3	207	330

3000K 38°



change without notice cambio sin previo aviso