

Minima R6 06W

MINIMA RX
recessed empotrado

608Lm / 2700K-4000K
IP40 / CRI ≥ 80 / 24° 38°

7lumen
create the light

DESCRIPTION DESCRIPCIÓN

Downlight with a "anti-glare effect" thanks to its very high position of the source of the source



GENERAL

negro black blanco white

recessed empotrado

Ip40

IK07

LIGHTING FIXTURE

APARATO DE ILUMINACIÓN

24° 38°

CRI ≥ 80

IP40

MacAdam ≤ 3

UGR <19

difusor transparente

clear diffuser

power values of the system (LED + driver): 6.5W

valores de potencia del sistema (LED + driver): 6.5W

ACCESSORIES ACCESORIOS

no disponible

not available

ELECTRICAL ELÉCTRICA

06W

220-240VAC 50/60Hz

equipo incluido

gear included

MEASURES MEDIDAS

día:83mm

altura: 39mm

height: 39mm

DIMMING REGULACIÓN

on / off

phase-cut dimming IGBT/TRIAC

corte de fase IGBT/TRIAC

1-10V

push

pulsador

DALI

CUTOUT RECORTE

día:75mm

min. espesor del techo: 13mm

min. ceiling thickness: 13mm

máx. espesor del techo: 44mm


max. ceiling thickness: 44mm

profundidad empotrada: 105mm

recessed depth: 105mm

REFERENCES REFERENCIAS

MINIMA R6/27	2700K	540Lm	90Lm/W
MINIMA R6/30	3000K	608Lm	101,4Lm/W
MINIMA R6/40	4000K	660Lm	109,8Lm/W



H(m)	D(cm)	Lux
1	45	2088
2	90	750
3	135	150

3000K 24°

H(m)	D(cm)	Lux
1	69	1650
2	138	540
3	207	128

3000K 38°



change without notice cambio sin previo aviso